



G-Touch® Sapphire

| | 65" 4K SAPPHERE | 75" 4K SAPPHERE | 85" 4K SAPPHERE |
|----------------------------|---|------------------------------------|------------------------------------|
| Product Code | TOU040010 | TOU040020 | TOU040030 |
| Backlight | LED | LED | LED |
| Display area | 1428.5 x 803.5mm | 1650.24 x 928.26mm | 1872 x 1053mm |
| Aspect Ratio | 16:9 | 16:9 | 16:9 |
| Native Resolution | 3840 x 2160 Pixel (4K) | 3840 x 2160 Pixel (4K) | 3840 x 2160 Pixel (4K) |
| Display colours | 8bit+FRC (1.07 billion colour) | 8bit+FRC (1.07 billion colour) | 8bit+FRC (1.07 billion colour) |
| Brightness | 350 cd/m2 | 350 cd/m2 | 350 cd/m2 |
| Response Time | 8ms | 8ms | 8ms |
| Refresh Rate | 60 Hz | 60 Hz | 60 Hz |
| Viewing Angles | 178° | 178° | 178° |
| Backlight Life | 30,000 Hours Typ. (Standard) 50,000 Hours Typ. (ECO model) | | |
| Glass Thickness | 4mm | 4mm | 3.2mm |
| Glass Hardness | 7 (Mohs) | 7 (Mohs) | 7 (Mohs) |
| Surface Treatment | New Generation Anti Glare | | |
| Touch Resolution | 32767 x 32767 | 32767 x 32767 | 32768 x 32768 |
| Touch Point | 20 Point | 20 Point | 20 Point |
| OS Support | Windows, Mac | Windows, Mac | Windows, Mac |
| Speakers | Front Facing 15Wx2 | Front Facing 15Wx2 | Front Facing 15Wx2 |
| PORTS | | | |
| Front Interface Inputs | HDMI 1.4(4K@30Hz) x1, USB(Touch) x1, USB 3.0(OPS) x2 MICx1 | | |
| AV Inputs | HDMI 2.0/1.4 (4K@60Hz) x2, VGA (1920x1080@60Hz)x1 VGA AUDIO x1 USB(Touch) x1 USB 2.0x1 | | |
| AV Outputs | AV Out x1 | AV Out x1 | AV Out x1 |
| Other | EAR PHONE x1, RS232 x1, YPBPR x1 AV Inx1 | | |
| OPS Slot | Yes 60Hz | | |
| Intelligent Light Detector | Yes | Yes | Yes |
| Multimedia | Image: JPEG, BMP, PNG / Video: MPEG2, MPEG4, H264, HEVC(H.265) / Audio: WMA, MP3, M4A, (AAC) | | |
| Power | Voltage AC 100-240V, 50/60Hz | | |
| Consumption | 250 (typ) < 0.5 W ("Standby Mode") | 400 (typ) < 0.5 W ("Standby Mode") | 450W(max) < 0.5 W ("Standby Mode") |
| Main Power Switch | Yes | Yes | Yes |
| Vesa Pattern | 600 x 400 | 800 x 400 | 800 x 400 |
| Operating Conditions | Temperature 0°C to 40°C | | |
| Humidity | 20% ~ 80% non-condensing | | |
| Dimensions | W1546 x H944 x D96mm | W1770 x H1071 x D101mm | W1982.6 x H1210.3 x D97.1mm |
| Single Box Packaging | W1670 x H1056 x D221mm | W1894 x H1193 x D247mm | W2119 x H1336 x D275mm |
| Weight | 45KG (Net) 65KG (Gross) | 59KG (Net) 77KG (Gross) | 69KG (Net) 86KG (Gross) |
| Package Contents | 1. Display 2. Power cable 3. USB cable 4. Remote control with batteries 5. Stylus (x1) 6. User Guide. Warranty Registration Document. | | |
| Software Included | SPARK II, Project Flow (60 DayTrial) | | |
| Warranty | 5 Year Warranty subject to registration within 28 days, terms and conditions apply. | | |

G-Touch® Sapphire Bundle


The solution that fits your needs



OPS unit



Genee Vision
Wireless Visualisers



Genee Premium High-Low
Mobile Trolley